


Materials

Body: Cast iron with black Duragard[®] E-coating Discs: M-19 Viton[®]

60VP-1001

Features

- 1" Female Connection to Both Dispenser and Underground Piping
- Multiple Mounting Methods mounting Boss accepts either U-Bolt or Straight Bolt mounting kits.
- Duragard[®] E-Coat Finish provides superior corrosion resistance.



OPW 60V Series Vapor Line Shear Valves

OPW 60VP-1001

Poppeted Vapor Save

- Double-poppeted design incorporated to help prevent vapor loss in the event dispenser is toppled
- CARB approved



OPW 60VSP-1001

Poppeted Vapor Saver

 Double-poppeted design incorporated to help prevent vapor loss in the event the dispenser is toppled

(VL)

CARB approved



 60VSPC-1001 features additional external threads on valve outlet for connection to a secondary containment system

Ordering Specifications

Product #	Connections	Poppeted
60V-1000	1" x 1" (3 x 3 cm) FNPT	
60VP-1001	1" x 1" (3 x 3 cm) FNPT	•
60VK-1002	U-Bolt Mounting Kit Includes: (2) ¾" (9.5 mm) U-bolts, (4) washers, (4) nuts	
60VK-1003	Straight Bolt Mounting Kit Includes: (4) ¾" (9.5 mm) 16 bolts, (4) washers, (4) nuts	

OPW 60VS-1000 Line Saver

 Shear section breaks on impact to minimize damage to underground piping.

OPW 60V-1000 Line Saver

 Shear section breaks on impact to minimize damage to underground piping. 60V Instruction Sheet Order Number: H12133M